

SIMATIC-Ka

Simatic 15_7
RELÉOVÝ

XC4		Interface	Vstupy			
V		1	4	I 0.0	RK A	
G		3	2	I 0.1	RK B	
+15V	A	7				
0V	D	5				
0V	B	stínění				
XC3		XC2	XC1			
			3	I 0.2	Res	
+15V	13		11	1	I 0.3	hydr. vpředu/SAC
0V	15		5	7	I 0.4	urychlení
			13	+24V L+		
				0V M_1M		
				I 0.5	Wb	
			12	I 0.6	LU	
			11	I 0.7	PU	
			2	I 1.0	UAC	
			6	I 1.1 POB		
		5	I 1.2 ZPS			
		4	I 1.3 PPS			
XC3			10	I 1.4	rychloposun vzad	
			9	I 1.5	rychloposun vpřed	
9	7		12	I 4.0	Enkodér KM A	
11	8		10	I 4.1	Enkodér KM B	
		Výstupy				
		7	Q 0.5		ruční	
		13	Q 0.6		KAC	
		8	Q 0.7		X>WSP	
			Q1.0		Z stop	
		11	Q1.1		X<WSP	
M752		XC3				
PUL-		4	SB	Q 4.0	KM Pulse	
zdroj	DIR-	1	SB	Q 4.1	KM Direction	
+24V	++	2				
+24V	++	3				
+24V	14	9				
+24V	8					
0V	6					

13.10.2015

13.10.2015